

# WEST Search History

DATE: Thursday, May 22, 2003

**Set Name Query**  
**side by side**

**Hit Count Set Name**  
**result set**

*DB=USPT,PGPB,JPAB,EPAB,DWPI,TDBD; PLUR=YES; OP=ADJ*

L9	L8 and l7	12	L9
L8	L6 and l5	12	L8
L7	L6 and l4	18	L7
L6	l3 and (pad or spacer or standoff) near (via or hole or thru hole or through hole)	20	L6
L5	L4 and leads	65	L5
L4	L3 and (component or device)	78	L4
L3	L2 and (spacer or pad or standoff) near ("3" or three or third)	83	L3
L2	L1 and (spacer or pad or standoff) near (edge or perimeter)	571	L2
L1	(pcb or printed circuit board) and (via or through hole or thru hole) and (spacer or pad or standoff)	22053	L1

END OF SEARCH HISTORY

# Searching PAJ

[MENU](#)[NEWS](#)[HELP](#)

Search Results : 0

[Clear](#)**Text Search**

If you want to conduct a Number Search, please click on  
the button to the right.

[Number Search](#)**Applicant, Title of invention, Abstract** — e.g. computer semiconductor

If you use the AND/OR operation, please leave a SPACE between keywords.

One letter word or Stopwords are not searchable.

AND

AND

AND

AND

AND

AND

**Date of publication of application** — e.g. 19980401 - 19980405 - 

AND

**IPC** — e.g. D01B7/04 A01C11/02

If you use the OR operation, please leave a SPACE between keywords.

[Search](#)[Stored data](#)

Copyright (C); 1998,2003 Japan Patent Office